

Drop bolt model 843

without profile cylinder hole, incl. striking plate (short)

Product description

The effeff 843 door deadbolt's compact design and sophisticated accessories enable it to be fitted in a variety of locations. It thus can offer optimum security as an additional door locking system in both commercial and private buildings.

Overview of Advantages

- For horizontal and vertical fitting
- When fitted horizontally, only possible to close downwards
- Can also be fitted to the surface of glass doors
- Automatic unlocking for 9 seconds via integrated control
- Integrated door and locking monitoring contacts
- Suitable for short and permanent release
- Suitable for swing doors

Technical data

Input operating voltage	12-24 V DC
Rated operating voltage tolerance range	± 15 %
12 V starting current	1250 mA
24 V starting current	1000 mA
12 V latching current	160 mA
24 V latching current	95 mA
Holding power	10000 N
Diameter dead bolt	12,7 mm
Bolt throw	16 mm
Distance between faceplate and striking plate	max. 6 mm
Housing length	164 mm
Housing width	22 mm
	39 mm
Installation position	Vertical and horizontally (closed downwards only)
Width face plate	25 mm
Face plate thickness	3 mm
Material faceplate	Stainless steel

Variants that can be ordered

Order number	Description
843-4-----Q41	Electric drop bolt (model 843) fail safe mode 12-24 V DC, incl. striking plate (short)
843-4-30----Q41	Electric drop bolt (model 843) fail secure 12-24 V DC, incl. striking plate (short)

